

# Decorative Blackboard

## Product properties

Full-matt chalkboard paint. Gives a surface with the same function as a chalkboard. Used wherever you want to be able to draw or write with chalk on the painted surface. Remove chalk residue with water.

- Chalkboard paint
- Easy to clean
- Easy to use



## Product use

Indoors, where you want a surface that looks and functions like a black chalkboard.

## Substrate

Must be clean, dry, firm and suitable for surface treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.

Dirt, grime, grease and chalking materials are removed with Fluren 37.

Water-soluble discolouration, nicotine and soot are cleaned with Fluren 49 and treated with Stop Primer.

Hard, smooth surfaces are sanded and primed as needed with Fix Primer.

Cracks, bumps and holes are filled.

Absorbent and porous surfaces are primed with Anchoring Primer

New or bare cleaned wood is primed with Stop Primer.

Metal is primed with corrosion inhibiting primer.

Priming is done with Combi Primer or Special Primer.

Apply at least 2 coats.

## Application

Brush or short-haired roller.

Stir thoroughly before and during use.

Apply wet on wet, finish by brushing/rolling in the same direction

Always use the same batch no. on continuous/broken surfaces

Cold/heat can affect the material viscosity.

Condensation must not occur.

Cold and increased humidity extend drying time, curing and recoat interval

Increased temperature and low humidity reduce drying time and through curing

Test on a small area to check adherence and the result.

## Expected result

Matt, covered surface.

Uniform even texture with low gloss.

Can withstand dusting and wiping with a damp cloth.

Does not block penetration from knots and water-soluble dyes, water marks and nicotine.

Carefully load the surface until the paint is fully cured.

**Please note!**

You can write with chalk on the painted surface after 3-7 days, depending on application conditions, layer thickness and substrate.  
The surface achieves full properties and function after 28 days of full curing.

**Environmental information**

Minimize your paint waste by pre-estimating how much paint you need.  
Remove as much paint as possible from tools before cleaning.  
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.  
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.  
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

**Storage**

Cool, frost-free and tightly closed

**Protection equipment**

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.  
Avoid inhalation of spray mist and grinding dust.  
Wear suitable protective equipment, see safety data sheet for further information.

**Technical Data**

Density (kgs/l)	1.3
Solids Weight %	53
Nominal spreading rate (m²/ltr.)	10
Long spreading rate (m²/l.)	12
Short Spreading rate (m²/ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	2
Recoatable at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water – does not normally need to be diluted
Cleaning of Tools etc.	Water and soap
Country of Origin	Poland

**Current TDS Version**

April 2025

**Replaces TDS Version**

November 2024

