

Stop spray

Product properties

Semi-matt, white special spray, that fast and efficient blocks stains of damp, nicotine, rust and soot as well as strokes from marker pens or other stains.

Product use

For use on walls and ceilings for effective blocking of colour strike-through. Used also on small areas of wood for blocking e.g. pen highlights etc.

Substrate

The substrate must be clean, dry and solid.

Treatment

Remove dirt, grime, grease and chalking materials with Basic Cleaner. Apply in several thin layers.

Application

Shake the can thoroughly and vigorously for at least 1 minute.
The ball must move freely in the can (heard clearly).
Spraying distance 35 - 40 cm.
Spray in a uniform, thin layer on the stains that should be sealed and let it dry between each layer.
Repeat the treatment until the stains have been completely sealed.
Drying time depends on air temperature, humidity and applied layer thickness.
After use, turn the can upside down and spray for several seconds.

Expected result

Sealed surface.
After drying, wallpaper can be hung or the wall can be painted with wall or ceiling paint.

Please note!

Carefully cover surfaces and areas that are not to be painted.
Ensure good ventilation.

Environmental information

Clean off the paint from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost-free and tightly closed



Technical Data

Product Type	Priming paint
Gloss	Semi Matte
Density (kgs/l)	0.83
Solids Weight %	32
Nominal spreading rate (m ² /ltr.)	2
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Fully cured at 20° C, 60 % RH (Days)	1

Current TDS Version

March 2023