



## SPACE Two Tone

DETALE CPH is a line of exclusive decorative products to take care of the small details. Paints and finishes are inspired by our Nordic design heritage and the changeability of nature. The products are suitable for professional as well as do-it-yourself use.



### Properties

Decorative product that produces a metallic look on walls and ceilings. Produces an artistic, two-tone effect. The product is applied to a fully filled, sanded and primed surface. Recommended for premises with medium functional requirements that are exposed to moderate dirt and wear and tear. For better dirt repelling properties and improved durability, Flügger Floor Varnish is recommended.

- **Two Tone metallic effect**
- **No drying time**
- **Velvety soft surface**

### Use

Living rooms, entrances, offices, business premises, clinics, shops, hotels and restaurants. The substrate must be filled using filler and then sanded and primed.

### Substrate

Must be clean, dry, firm and suitable for surface treatment.

### Treatment

Remove loose material and paint by cleaning, sanding and dusting.  
Remove dirt, grime, grease and flaking material by cleaning thoroughly.  
Sand flat hard, slippery surfaces.  
Apply medium filler and smooth out.  
The surface is sanded, cleaned and primed using primer before further treatment.  
It is important that the surface is thoroughly sanded so it is 100% even and uniform.

### Application

Apply using a wide spatula in an ultrathin, covering layer.  
Do the entire wall at one time without stopping.  
Decide your choice of tools based on the size of the surface.  
Avoid condensation formation.  
Always test for control and acceptance of adhesion and result.

## Expected result

Metallic appearance.

The surface does not become rock hard, and it is therefore susceptible to bumps and scratches.

Withstands dusting and light cleaning with a damp cloth.

Take care placing loads on the surface before the paint is fully cured.

## Usefull Information

The product is designed as a one-coat solution, but if you don't get the desired look, an extra coat can be applied.

## Environmental information

Clean off the paint from tools and wash them with water. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

**Storage:** Cool, frost free and tightly closed

## Technical Data

Long spreading rate (m <sup>2</sup> /l)	10
Short Spreading rate (m <sup>2</sup> /l)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Cleaning of Tools etc.	Water

### Current TDS Version

December 2021

### Replaces TDS Version

July 2021